




MP

RÉSEAU
ON
GPL

TÉ DE RACCORDEMENT POUR TUBE PE



CARACTÉRISTIQUES TECHNIQUES

Normes : NF EN 1555-3+A1
Température : -20°C à +60°C

| CALIBRE | CONNEXION PE | CONNEXION PE | CONNEXION PE | L1 | L2 | P | H1 | MARQUE | RÉF. |
|----------|--------------|--------------|--------------|-----|-----|---------|-----|--------|----------|
| 15/15/15 | PE Ø 20 | PE Ø 20 | PE Ø 20 | 114 | 57 | 27 | 75 | | 1080-051 |
| 25/15/25 | PE Ø 32 | PE Ø 20 | PE Ø 32 | 110 | 55 | 41 | 89 | | 1080-081 |
| 25/25/25 | PE Ø 32 | PE Ø 32 | PE Ø 32 | 110 | 55 | 41 | 87 | | 1080-053 |
| 32/15/32 | PE Ø 40 | PE Ø 20 | PE Ø 40 | 180 | 90 | 32 / 46 | 118 | | 1080-082 |
| 32/25/32 | PE Ø 40 | PE Ø 32 | PE Ø 40 | 180 | 90 | 41 / 46 | 118 | | 1080-084 |
| 32/32/32 | PE Ø 40 | PE Ø 40 | PE Ø 40 | 180 | 90 | 46 | 122 | | 1080-058 |
| 50/32/50 | PE Ø 63 | PE Ø 40 | PE Ø 63 | 230 | 115 | 46 / 65 | 154 | | 1080-083 |